

FREE HEAT Series



FREE HEAT 303
3 Collector | 300 (L)



FREE HEAT 302
2 Collector | 300 (L)



FREE HEAT 182
2 Collector | 180 (L)



FREE HEAT 181
1 Collector | 180 (L)

Solahart
super-shield™
ENAMEL TANK PROTECTION

FITUR UTAMA

- Solahart Super-Shield™ perlindungan tangki enamel
- Garansi Solahart Terpercaya
- Ramah lingkungan
- Pemeliharaan mudah dan operasi yang handal
- Tersedia booster listrik

CAPACITY

300 (L)

180 (L)

*ONLY SHOWER

FAMILY SIZE

6 people

4 people



GOLD J 303
3 Collector | 300 (L)



GOLD J 302
2 Collector | 300 (L)



GOLD J 182
2 Collector | 180 (L)



GOLD J 181
1 Collector | 180 (L)

GOLD J Series



13 Alur Kolektor



Blue Sputtered



PERFORMA TERTINGGI



RAMAH LINGKUNGAN



TAHAN CUACA DINGIN



MENGURANGI PENGGUNAAN ENERGI



35 Alur Kolektor



Black Polyester

10 TAHUN

GARANSI TANGKI

10 TAHUN

GARANSI KOLEKTOR

1 TAHUN

GARANSI SPARE PARTS

5 TAHUN

GARANSI TANGKI

5 TAHUN

GARANSI KOLEKTOR

1 TAHUN

GARANSI SPARE PARTS

System	181 JBT	302 JBT		Tank	180	300		Collector	JBT	
Weight (full)	301	498	Kg	Capacity	180	300	L	Aperture Area	1.86	m²
Weight (empty)	111	184	Kg	Weight (full)	248	404	Kg	Capacity	2.1	L
Length	2.475	2.475	m	Weight (empty)	68	104	Kg	Weight (full)	33	Kg
Height	0.51	0.51	m	Height	0.51	0.51	m	Weight (empty)	31	Kg
Width	1.62	2.31	m	Length	1.494	2.31	m	Length	1.941	m
Working Pressure	1.000	1.000	kPa	Cylinder Material	Steel, low carbon, 2.5 mm (0.1")			Depth	0.08	m
Collectors	1	2		Cylinder Lining	Primaglaze Ceramic Lining, 2 Coats			Width	1.023	m
Reservoir Tank	✗	✓		Insulation	Polyurethane Pressure Injected Foam			Working Pressure	1.400	kPa
				Case	Aluminium: 0.4 mm (0.2")			No. Of Riser	13	
				End Caps	Polypropylene: carbon black, UV stabilised			Riser Material	Copper	
				Anode	Magnesium, sacrificial, with steel core			Absorber Material	Copper	
				Auxiliary Electric Booster	Type: Copper sheath, immersion Rating (kW): 1.0, 1.8, 2.4, 3.0, 3.6, 4.8 Supply Voltage: 220V - 250V			Absorber Surface	Sputtered selective surface	
								ray Material	Aluminium 0.65 mm	
								ray Insulation	Glass Wool 50 mm	
								Collector Cover	Low Iron Solar Tempered Glass 3.2 mm	

System	G 181 J	G 302 J		Tank	180	300		Collector	Gold J	
Weight (full)	299	502	Kg	Capacity	180	300	L	Aperture Area	1.86	m²
Weight (empty)	115	194	Kg	Weight (full)	248	404	Kg	Capacity	3.8	L
Length	2.55	2.55	m	Weight (empty)	68	104	Kg	Weight (full)	46	Kg
Height	0.510	0.510	m	Height	0.51	0.51	m	Weight (empty)	42	Kg
Width	1.8	2.79	m	Length	1.494	2.31	m	Length	1.941	m
Working Pressure	1.000	1.000	kPa	Cylinder Material	Steel, low carbon, 2.5 mm (0.1")			Depth	0.08	m
Collectors	1	2		Cylinder Lining	Primaglaze Ceramic Lining, 2 Coats			Width	1.023	m
				Insulation	Polyurethane Pressure Injected Foam			Working Pressure	1.200	kPa
				Case	Aluminium: 0.4 mm (0.2")			No. Of Riser	35	
				End Caps	Polypropylene: carbon black, UV stabilised			Riser Material	Steel	
				Anode	Magnesium, sacrificial, with steel core			Absorber Material	Steel	
				Auxiliary Electric Booster	Type: Copper sheath, immersion Rating (kW): 1.0, 1.8, 2.4, 3.0, 3.6, 4.8 Supply Voltage: 220V - 250V			Absorber Surface	Polyester Powder Coat	
								Tray Material	Aluminium 0.65 mm	
								Tray Insulation	Glass Wool 50 mm	
								Collector Cover	Low Iron Solar Tempered Glass 3.2 mm	





INDIRECT SERIES

Sistem kerja pemanasan air Solahart Indirect Series tidak secara langsung, air didalam tangki dipanaskan oleh media pemanas, media tersebut bersirkulasi (thermosiphon) pada jacket tank (closed circuit). Disaat melalui jacket tank media pemanas tersebut memanaskan air yg disimpan dalam tangki air panas yang akan digunakan keluarga anda.



Jutaan Pengguna

Solahart telah dipakai lebih dari 3 juta orang di 126 negara



Kualitas Terbaik

Solahart Indirect Series dirancang untuk tahan terhadap segala kondisi dan iklim



Quality Control

Setiap komponen Solahart diuji dengan ketat sebelum sampai kerumah anda



Jaringan Luas

Solahart memiliki jaringan penjualan lebih dari 50 dealer di seluruh Indonesia dan team penjualan dan engineering yang sudah terbukti selama puluhan tahun.

@SolahartIndonesia

Solahart Indonesia

Solahart Indonesia

Solahart Indonesia



www.solahart.co.id



DST15/BU/AGU/2024



INDIRECT SERIES

